

GOVERNMENT OF INDIA MINISTRY OF RAILWAYS (RAILWAY BOARD)

No.2010/Safety(A&R)/19/13

New Delhi, dated 16.07.2010

Chief Operation Manager, North Central Railway, Allahabad

Sub: Crossing of trains at stations provided with one platform line.


Ref: Your letter No.T/Gen./G&SR/Amend/05/05 dated 01.07.2010.

The letter under reference has been examined wherein it has been requested to issue guidelines regarding berthing of passenger trains during crossing of two trains at stations provided with one platform. It has been decided that it may not be appropriate to issue uniform guidelines applicable for all stations and all situations. As layout, platform heights, volume and type of traffic, etc. differ from station to station, it would be better if berthing of passenger trains be decided based on local conditions prevailing at the stations. Therefore, the berthing of passenger trains may be prescribed in the Station Working Rules of each station. The relevant SR may be modified to facilitate this.

It is also mentioned that in the draft of proposed General Rules submitted by GRRC, the procedure to be followed during crossing and/or precedence involving passenger trains has been proposed to be prescribed in the SWR of respective station keeping in view the number, length and height of platform(s) as well as other local conditions at the station.

Further, it is emphasised that the modification of the Subsidiary Rules is within the competence of the authorised officer of the Railway (COM) without reference to the Board, provided it does not contravene any of the provisions of the GR. The Railway may, if considered necessary and safe, adopt the system of crossing of two trains as proposed in para 3 of the letter under reference, at stations/locations where such an exception is warranted.

2 412) STOR STORY STORY



(J.S. Bindra) Joint Director/Safety Railway Board



Kamlesh Gupta Adviser (Safety) भारत सरकार
रेल मंत्रालय, (रेलवे बोर्ड)
नई दिल्ली-१९० ००९
GOVERNMENT OF INDIA
MINISTRY OF RAILWAYS
(RAILWAY BOARD)
NEW DELHI-110001

D.O. No. 98/Safety(A&R)/19/16/Loose

Dated 12.07.2010 ,

Dear Shri Mittal.

Sub: Fog Vision Instrumentation Project under TMRS.

Ref: RDSO's letter No. R2/163/TMRS/Proj. dt. 30.09.09.

Board (MT, ML and CRB) had expressed concern over the inadequate visibility, during foggy conditions, of the colour light signals (MAUQ Signals) as also of the Tail Lamps. Dense fog have resulted in three collisions on Allahabad Division during January 2010, hence the concern of the Railway Board to bring in improvement in the above.

For improving visibility of colour light signals, a project had been undertaken recently by RDSO under Technology Mission for Railway Safety (TMRS). Unfortunately RDSO has recommended that the TMRS project to be closed despite no headway having been made in improving visibility of MAUQ Signals.

For improvement of visibility of the Tail Lamp, RDSO is already working on it. In this regard a letter dated 29.06 10 (copy enclosed) has already been addressed to you.

I am enclosing in Annexure, relevant extracts of the correspondence between RDSO and the E&R Directorate, Railway Board on the subject under reference (TMRS).

Your intervention is requested to expedite the above matters.

With best wishes,

Yours sincerely.

Encl.: As above

(Kamlesh Gupta)

Shri K.B. L. Mittal, Director-General RDSO, Lucknow -226011.

PIC

12-07-2010

Emistry Carlotter Tolling of the Control of the Con



भारत सरकार रेल मंत्रांलय, (रेलवे बोर्ड) नई दिल्ली-११० ००१ **GOVERNMENT OF INDIA** MINISTRY OF RAILWAYS (RAILWAY BOARD) NEW DELHI-110001

D.O. No. 85/Safety-I/24/2

New Delhi dated 29.6.10.

Dear Shri Mittal.

Sub: Improved visibility of Portable Battery operated Tail Lamp by use of Laser LEDs.

Ref: Your letter No. 2001/TR/281/HSTL/Part IV dt. 1.7.2009

The Portable Battery Operated LED based Tail Lamp does not have adequate visibility as required during Fog; its visibility may be even less as compared to the earlier version as has been stated at certain levels. The issue came up on a reference first made by ML in the GM's Conference held in the beginning of the current year. It is of paramount importance that the visibility of the Flashing Red Aspect of the Tail Lamp is for as much a distance as possible. This is especially necessary during the months having foggy weather.

RDSO had been advised vide our letter dated 25.2.10, (copy enclosed) to review the specifications and take the following action:-

- Change/improve the specification of Tail Lamps so as to do away with the Amber (Yellow) aspect Improve visibility by use of Laser Type LEDs and other changes in specification. Examine reduction in the weight and size of the Tail Lamp as a consequence of above.
- Proto type Inspection for Vendor development for Portable Tail Lamps may be considered after action is taken on item above.

Views of some of the Railways on the Proto Type on the two types of tail lamps developed by RDSO have been received. The feed back of the zonal railways i.e. NCR ,SECR, SC Railway; S.Rly ,EC Railway and WCR is enclosed.

In view of the urgency of bringing improvement in the visibility of the Tail Lamp before the onset of the Foggy weather, I would request for early finalization of improved specs.

Encl: As above.

Shri K.B. L Mittal, DG/RDSO Lucknow.

सर्वामक हाइस जाची **Signature**

Yours sincerely,

(Kamlesh Gupta)

GOVERNMENT OF INDIA/BHARAT SARKAR MINISTRY OF RAILWAYS/RAIL MANTRALAYA (RAILWAY BOARD)

No.2003/E&R/3400/20/TMRS(Pt:V)

New Delhi, dated 05.02.2010

The Director General, RDSO, Manak Nagar, <u>Lucknow.</u>

(Kind Attn: ED/Research/RDSO)

Sub: Fog Vision Instrumentation project under Technology Mission on Railway Safety.

RDSO vide letter No.R2/163/TMRS Project dated 30.09.2009 had advised that the TMRS Mission has been completed though no solution has been found on Fog-Vision Instrumentation. Fog has resulted in 3 major accidents on IR and it is thus imperative that this work can not be closed without finding a solution, as it is very critical for Railways. In this regard Board has observed as under:—

"There is an urgent need to make our colour light/MAUQ signals effective during foggy conditions. Alongwith this we may redesign the tail lamps – fixed ones of SLR or those with the Guards, so that they are effective during fog."

Further, Ministry of Earth Sciences (MoES) and Indian Meterological Deptt. (IMD) are involved in fog dispersal experiments for improving the visibility. RDSO may co-ordinate with them and an effective solution be found of this important Technology Mission Project. In this connection copy of a note from Adv./Safety is enclosed alongwith relevant annexures.

(Gaurav Agarwal)

Director, Effy. & Resarch (ME)
Railway Board

Encl: As above.

plisant feely

Railwing Formation of Leave

GOVERNMENT OF INDIA\BHARAT SARKAR MINISTRY OF RAILWAYS/RAIL MANTRALAYA (RAILWAY BOARD)

No.2003/E&R/3400/20/TMRS

New Delhi, dated 20.1.2004

The Director General, RDSO, Manak Nagar, Lucknow.

(ii)

Sub: Technology Mission on Railway Safety.

Ref: DG/RDSO's D.O. letter NoR2/145/MAEC/CSP dated 9.12.2003.

Please refer to your D.O. letter mentioned above. A list of nodal officers from Board's office, project-wise for the above Mission, as approved by the is enclosed for information please.

> (R.K. Tandon). Executive Director, Effy. & Resarch Railway Board

EDME/Chg., EDME/Tr.

ED/Track, ED/Sig.

EDME/Fr.

EDEE/RS

NODAL OFFICERS LIST FOR PROJECT APRROVED BY BOARD UNDER TECHNOLOGY MISSION ON RAILWAY SAFETY

S.No	. Project Description	Nodal Officer (ED	
	9	Level) for each project at Board's Office	1
	Mission Program 1 - Traction and Rollin	g Stock	
1.	Track Side Bogie Monitoring System	EDME/Chg.	
2.	Derailment Detection Devices	EDME/Tr.	
3	Sensors for Detecting Hotboxes, Hot Wheels	EDME/Fr.	AM/ME
4	On Board Diagnostics	EDEE/RS.	
5	Wheels and Axles of Improved Metallurgy	EDME/Fr.	
6	Measuring Wheel Technology	EDME/Fr.	
-	Mission Program 2 - Tracks And Bridges		
7.	Corrosion Prevention Of Rails	EDCE/P	
8.	Improved Rail Fastening	ED/Track	AM/CE
9.	Rail Flaw Detection Instrumentation	ED/Track	
10.	Environmental Friendly Coach Toilet	EDME/Chg.	-
	Discharge System		
	Mission Program 3 - Signals And Commu		
.11.	Solid State Interlocking	ED/Sig.	
12.	Satellite Imaging for Rail Navigation (SIMRAN)	ED/Sig.	
	(i) GPS based Rail Network Mapping and Train Tracking (ii) Wireless connectivity		AM/Sig.
	Computer Aided Remote Controlled	ED/Sig.	
. 1	Signaling and		
	Train Describer System with Display Panels		
14.	Mission Program 4 Fog-Vision	ED/Sig.	AM/Sig.
	Instrumentation		3
-			

टेलीफोन /Tele ·

2451200 (PBX)

.

2450115 (DID)

ਮੈਰਨ ∕Fav

91-0522-2458500



गारत सरकार - रेल नंत्रालय अनुसंधान अभिकल्प और मानक संगठन लखनज - 226 011 Government of India-Ministry of Railways Research Designs & Standards Organisation

Lucknow = 225 014

AN ISO 9001 CERTIFIED ORGANISATION

No. R2/163/TMRS Projects Vol.IV

Dt. 26.10.2009

The Executive Director/E&R Railway Board,
New Delhi


Sub: Technology Mission on Railway Safety Report.

Ref: Director/E&R/Railway Board's letter no. 2003/E&R/3400 /20/TMRS (Pt.) dated 13.03.2008.

In reference to Board's letter quoted above, TMRS Progress report for the quarter ending July-September 2009 is being sent herewith.

DA: As above.

(M K Agrawal)
Exe. Director Research







		ないと表記し					***	
	آ د ر	di la emaK jor	1	· -	Work done during the	Work plan	ned for herr	Adequacy of
	≖्य गं	Project	comme		draitei	up gu	ETTER	the work fore
		:	t_ t_/		1			so far to adher a
			Date of complet	i				:
			ion		i ,			PDC ≃
	-			RTTIS(Based upon SIMRAN)		<u> </u>		
				covering Loco Equipment,	ĺ			
	1			Station Equipment, Coach Display Equipment.		1		
	İ			Display Equipment, Integrated PA System and				
	-	.•		Central Server has been				
				prepared and issued under RDSO/SPN/TC/77/2008.		-		·
				• As desired by Railway				
				Board Field Trial of Onboard				
				Passenger Information Display System integrated				
		Í		with SIMRAN System have				
				been successfully completed				
				in Gomati Express and reported to Railway Board.				
		•		• As desired by Railway				
				Board, Field Trial of Station				
				Passenger Information Display System integrated				
				with SIMRAN System has				
] [been successfully conducted at Patna Junction Railway				
			1	Station and reported to				
	ļ			Railway Board.		-		
	- Section 1			•				
f	4.	Fog Vision	13 1	Field trial with BEL's	· Payment made to firm in	NIL- since	Not	Due to reasons
(Instrumen tation		thermal imager completed. Result not positive.	august itself but detector	TMRS	adequate	mentioned in
	1		-	Full fledged fog chamber	not yet arrived. Expected to arrive NOV 09.	project closed.	with respect to	previous column and also in
			Sep 2009 •	made & fully operational.	• Lens received and		original	absences of any
			2009	Systematic study of fog attenuation for 1.55 µm	mounted in Sep 09. Images of objects placed		PDC as initial	other known technique
				wavelength shows	in fog environment		trails with	available to
				negligible advantage over visible He-Ne (0.63 µm).	created inside fog		thermal	achieve original
			•	All tunable laser	chamber has been obtained and		imager had failed.	objectives. It has decided in MICC
]		measurements have been	demonstrated during last		Also the	meeting on 3m
			-	competed however it does not indicate that 1.55	MICC on 6t Aug 09.these images were obtained in		experimen ts with	DEC.08 ii, demonstrate the
Į				microns would be usable	visibility of <10cm for an		1.55	proof of concept
		ŀ		for FOG vision. Two approaches have been	object distance of 1.2 m this corresponds to >		micron laser have	by displaying
				theoretically arrived at for	250m distance vision for		not	image in the fog chamber , and
			}	usage of longer	an object of a couple of		succeeded	outside the fog
				wavelengths (CO2). For pilot measurements in	feet in dimensions under an atmospheric fog			chamber instead of an onboard
Ì				the fog chamber a 10W	visibility of 50m.			implementation.
1				CO2 laser has been procured.	 Software developed to display the image on line 			Though the proof of concept has
	1		•	A scanning system suitable	directly from the			been
		•		for usage alongwith the fog	acquired data however			demonstrated in
	.			chamber, has now been fabricated for the CO2	its implementation is delayed. Since iit does			the lab in fog chamber the
				laser.	not still have the license			making of
		i.	•	The normal glass windows	for lab view "image			working
	İ			fitted at both ends of the fog chamber were replaced	series" Of NI request has been placed to NI for the			prototype for demonstration in
	Í			with high transmitty ZN-Se	same.			field requires
	}	1		window suitable for 10.6	• The lens has been			further research development and
				Micro-bolometer based	mounted in front of IR	İ		time.
	1			uncooled IR detector made	laser and a field during a			An order for the
		-		of Ti was procured & used in experiments.	field experiment in IIT, spot could be focussed to		•	detector has been placed which as
			•	Vacuum housing was made	an 8 inch diameter at a		:	vet to arrive. The
			1 :	for detector.	distance of 120m. The requirement is that this			lens improving
				The fog attenuation is 1/45th of that of visible He-	spot size should be			image can :,:
	.		1 :	NE laser	lcm*1cm at 400m. The spot size measurement at			tried only are detector has been
į	1	İ	•	Scattering from Rail track objects such as stone rail,	larger distances has	.		received.

র স	Name of the	ai Dama - 21	A 7.2 4.1			•	24
		comme ncemen t / Date of complet	previous quarter	Work done during the quarter	Work planne	d for Bearing	Adequacy of the work dong so far to adher to the given PDC
		•	and fasteners surface have been measured from one angle. The required peak laser at 10.6 µm for a distance of 400m for a visibility condition of 50m is around 5.3W whereas the power required at 1.55 µm is in the range of 100MW, which is very high. At 5.3W of 10.6 µm wavelength the exposer time should not be greater than 1ms for human safety and so pulsed CO2 laser is the solution. The detector has been procured from US firm. For 2D scanner(x-y) has been procured	become difficult as the power becomes comparable to the sensitivity of the detector which at present time is not in safe operational condition.			Meanwhile TMR: project: as a whole has beer closed including this project.

^{14&}lt;sup>th</sup> MICC meeting held at IIT Kanpur on 06.08.2009 during the quarter.